

SAFETY DATA SHEET

MULTI-WIPE SOLVENT

Issued: 08/08/2005

Revision No: 1

Page 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: MULTI-WIPE SOLVENT

Product code: M01780

Company name: Image Chemical Products Ltd

3 Barnfield Way

Altham Business Park

Altham
Accrington
Lancashire
BB5 5YT

Tel: +44 (0)1282 777200

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DISTILLATED PETROLEUM SPIRIT 10-30%

[Xn] R65; [Xi] R66
• XYLENE 50-80%

EINECS: 215-535-7 CAS: 1330-20-7 [-] R10; [Xn] R20/21; [Xi] R38

3. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation and in contact with skin. Irritating to skin. Harmful: may cause lung

damage if swallowed. Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may

occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the

affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a

doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to

drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

Issued: 08/08/2005

SAFETY DATA SHEET

MULTI-WIPE SOLVENT

Page 2

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking

containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by

an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: XYLENE

TWA 220 mg/m3 STEL 441 mg/m3

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless
Odour: Unpleasant

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Viscosity: Non-viscous

Issued: 08/08/2005

SAFETY DATA SHEET

MULTI-WIPE SOLVENT

Page 3

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: XYLENE

ORL MUS LD50 2119 mg/kg ORL RAT LD50 4300 mg/kg SCU RAT LD50 1700 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1993 ADR Class: 3

Packing group: III Classification code: F1

Shipping name: FLAMMABLE LIQUID, N.O.S. (XYLENE)

Labelling: 3 Hazard ID no: 30



IMDG / IMO

UN no: 1993 Class: 3

Packing group: III EmS: F-E,S-E

Marine pollutant: . Labelling: 3

Issued: 08/08/2005

SAFETY DATA SHEET

MULTI-WIPE SOLVENT

Page 4

IATA / ICAO

UN no: 1993 Class: 3

Packing group: III Packing instructions: 309(P&CA); 310(CAO)

Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Harmful.

Risk phrases: R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.

S36/37: Wear suitable protective clothing and gloves.

S46: If swallowed, seek medical advice immediately and show this container or label.

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.